

SPiiPlusEC

Powerful Motion Controller and EtherCAT® Network Manager

- Up to 64 fully synchronized axes
- Up to 5KHz rate of profile generation and EtherCAT cycle
- NetworkBoost™ network failure detection and recovery with ring topology
- Up to 1GbE Ethernet host communication
- Open Architecture - ACS' and other vendor's EtherCAT devices, drives and I/O
- Comprehensive set of support tools for EtherCAT Network setup, axis tuning, application development, and diagnostics

ACS' SPiiPlusEC is a state of the art line of Motion controllers and EtherCAT master.

It is specifically designed to extend the capabilities of the SPiiPlus line of controllers and etherCAT master, to address the needs of modern machinery for cost effective high performance multi-axis, scalable and distributed control of motion centric applications. The SPiiPlusEC open architecture operates in conjunction with ACS' line of EtherCAT servo and step motor drives and I/Os modules, as well as with any certified third party EtherCAT module that complies with CAN over EtherCAT (CoE) protocol. The unique NetworkBoost™ optional feature increases machines' uptime using ring topology based redundancy to continue operation upon a network failure.

The SPiiPlusEC EtherCAT cycle and profile generation rate is 1 to 5kHz. ACS drives execute the servo control algorithms at a 20kHz rate using a distributed clock to ensure synchronization of better than 0.1 microsecond between all axes.

The SPiiPlusEC is complemented by the SPiiPlusNT suite of software tools that are designed to minimize time to market and to address the specific machine requirements throughout its whole life cycle. It provides extraordinarily easy automatic network setup, fast host and embedded application development, and quick diagnostics. Set up of third party drives are done using by the third party tuning tools. Once connected to the EtherCAT network, real time variables, such as position, position error, velocity and others can be viewed, monitored and recorded with ACS' tools. All tools include a built-in simulator, powerful remote access and diagnostics, and fast error recovery, reducing training effort and costs.

CE Pending

EtherCAT® is registered trademark and patented technology, licensed by Beckhoff Automation GmbH, Germany

Contact us: sales@acsmotioncontrol.com | www.acsmotioncontrol.com



Specifications

Number of Axes

Up to 64 axes, Thousands of I/O's

Motion Types

- Multi-axis point-to-point, jog, tracking and sequential multi-point motion
- Multi-axis segmented motion with look-ahead
- Arbitrary path with PVT cubic interpolation
- Third order profiles (S-curve)
- Smooth on-the-fly change of target position or velocity
- Inverse/Forward kinematics and coordinate transformations (at application level)
- Master-slave with position and velocity locking (electronic gear/cam)

Programming

- ACSPL+ powerful motion language
 - Real-time program(s) execution
 - Up to 64 simultaneously running programs
- IEC61131-3 (PLC) languages: IL, ST, LD, FBD, SFC
- NC programs (G-code)
- C/C++, .NET and many others standard languages

Supported EtherCAT Modules

All ACS EtherCAT network modules. Refer to ACS web site for an updated list of modules www.acsmotioncontrol.com/products.

Non ACS Modules

ACS qualifies drives and I/O modules made by other vendors Refer to ACS web site for an updated list of other vendor's supported modules www.acsmotioncontrol.com/downloads Other vendor's drives supported mode is Cyclic Synchronous Position (CSP). Additional modes are supported by some drives. Contact ACS for details: sales@acsmotioncontrol.com

Communication Channels

Serial: two RS-232. Up to 115,200 bps

Ethernet: One, TCP/IP, 100/1000 Mbps

Simultaneous communication through all channels is fully supported. Modbus as master or slave is supported over Ethernet and serial channels. Ethernet/IP protocol as adapter is supported over Ethernet channel.

EtherCAT ports

Two ports, Primary and secondary

Rate: 100 Mbit/sec

Protocols: CoE and FoE

NetworkBoost™ (optional) - Automatic network failure detection and recovery using ring topology and redundancy ring topology and redundancy

Ordering Options

	Field	Example selection by user	Optional Values
Maximum number of axes	1	04	2,4,8,16,32,64
ECAT 3rd party Servo Drive	2	00	Up to the maximum number of axes
ECAT 3rd party Step motor Drive (open & closed loop)	3	00	Up to the maximum number of axes
ECAT 3rd party IO EtherCAT node	4	04	4 (included automatically FOC), 8,16,32,64
PLC (IEC-61131-3), G-Code, or both	5	N	None (N), PLC only (Y), G-code only (G), Both (B)
ServoBoost, number of axes supported	6	A	0(N),4(A),8(B),12(C),...60(P),64(Q)
Input shaping	7	Y	Yes (Y), No (N)
Maximum MPU cycle rate (kHz)	8	D	Default (D),4kHz (4), 5kHz (5)
NetworkBoost - Ring topology, cable failure detection & recovery	9	N	None (N), NetworkBoost (A)
Default # of ACSPL+ buffers/tasks	10	D	Default (D), 16 (A),32(B), 64(C)

Example: SP+EC04000004N04YDND

Field	1	2	3	4	5	6	7	8	9	10	
PN	SPIIPlusEC	04	00	00	04	N	A	Y	D	N	D

MPU

Processor: Intel® Atom™ N2600 1.6 GHz

Memory: RAM- 1Gb , Flash NV memory- 1Gb

Product	Maximum Number of Axes	ACSPL+ Buffers/tasks	Controller Cycle Time (msec)				
			1	0.5	0.25	0.2	Default Value
SPIIPlus EC-02-...	2	10	$\sqrt{1.2}$	$\sqrt{1.2}$	$\sqrt{1.2}$	$\sqrt{1.2}$	0.5
SPIIPlus EC-04-...	4	10	$\sqrt{1.2}$	$\sqrt{1.2}$	$\sqrt{1.2}$	$\sqrt{1.2}$	0.5
SPIIPlus EC-08-...	8	10	$\sqrt{1.2}$	$\sqrt{1.2}$	$\sqrt{1.2}$	$\sqrt{2.3}$	0.5
SPIIPlus EC-16-...	16	16	$\sqrt{1.2}$	$\sqrt{1.2}$	$\sqrt{2.3}$	-	0.5
SPIIPlus EC-32-...	32	32	$\sqrt{1.2}$	$\sqrt{1.2}$	-	-	0.5
SPIIPlus EC-64-...	64	64	$\sqrt{1.2}$	-	-	-	1

- 1- Extended Segmented Motion (XSEG) with no limitations. User should check that USAGE < 80%.
- 2- NetworkBoost limitations: CTIME = 1 msec - up to 64 axes. CTIME = 0.50 msec - up to 24 axes. CTIME = 0.25 msec - up to 8 axes. CTIME = 0.20 msec - up to 4 axes
- 3- Extended Segmented Motion (XSEG) with limitations: Segment length > 5 ms. IMM VEL = ... command shouldn't be used

Power Supply

24Vdc ± 10%, 0.8A

Environment

Operating Temperature: 0°C to 55°C

An internal fan is automatically activated when operating temperature rises above 30°C

Storage Temperature: -20°C to 85°C

Humidity: 90%RH, non-condensing

Dimensions

175 x 124 x 45.5 mm³

Weight

450 gr.

Accessories

Din rail mounting kit: Part Number DINM-15-ACC